



Generally the firmware version of the mecablitz 58 AF-1 digital is displayed after switching-on. Thereby the version can be seen in the display on the right side under the Metz logo.

Basically the current firmware version also includes the modifications and improvements of former firmware versions. The basic improvements of the mecablitz 58 AF-1 digital for Canon and Nikon normally are included in the firmware of the other flash units for Olympus, Pentax and Sony.

| mecablitz 58 AF-1 digital for | Firmware version | Released on: | Reason of modification: |
|-------------------------------|------------------|--------------|---|
| Canon | 1.2 | | Canon |
| | 2.0 | 10.08.2007 | Now also for Canon Power Shot S5 IS, EOS 1D Mark III and EOS 40D. Improvements: 1. Triggering by entre contact is possible. 2. Operation of second reflector in E-TTL mode enhanced. 3. Repeat function of the last changed parameter. 4. Beep signal shorter. |
| | 2.1 | 09.07.2008 | Improvement: Operation of remote master mode enhanced. |
| | 3.0 | 17.07.2009 | Improvements: 1. Select menu is extended by AF measuring beam on/off 2. The custom functions and flash modes also can be set by the menu of the current cameras. |
| | 3.2 | 24.02.2010 | Improvements: 1. Flash distance also is shown at high ISO values. 2. Operation of remote mode enhanced. |
| Nikon/Fuji | 1.2 | | Nikon |
| | 2.0 | 10.08.2007 | Now also for Nikon D40 and D40x. Improvements: 1. Repeat function of the last changed parameter. 2. Beep signal shorter. |
| | 3.0 | 20.05.2008 | Now also for Nikon D3. Improvements: 1. Operation of second reflector in E-TTL mode enhanced. 2. Start signal in remote master mode changed from second reflector to main reflector. |
| | 4.0 | 09.10.2008 | Now also for Nikon D700. |
| | 4.1 | 28.09.2009 | Improvements: 1. Zoom-Size function possible. 2. Setting of the parameter values by repeat key. 3. Select menu is extended by AF measuring beam on/off. |



| mecablitz 58 AF-1 digital for | Firmware version | Released on: | Reason of modification: |
|-------------------------------|------------------|--------------|---|
| Olympus/Panasonic | 1.2 | | Olympus/Panasonic/Leica |
| | 2.0 | 16.06.2008 | Now also for Panasonic DMC-L10 and for RC-mode with Olympus E-3, E-420, E-520, SP-570. The Olympus RC-mode replaces the previous remote mode. Improvement: Operation of second reflector in TTL mode enhanced. |
| | 2.1 | 25.06.2009 | Improvement: Operation of remote mode enhanced. |
| Pentax/Samsung | 1.0 | | Pentax/Samsung |
| | 1.1 | 30.12.2009 | Improvements: 1. Operation of second reflector enhanced. 2. Start signal in remote master mode changed from second reflector to main reflector. 3. Setting of the parameter values by repeat key. |
| Sony | 1.0 | | Sony/Konica Minolta |
| | 2.0 | 20.05.2008 | Now also for Sony A300 and A350. Life view mode in normal und remote mode is supported. |
| | 3.0 | 24.02.2010 | Improvements: 1. Zoom-Size function possible. 2. Setting of the parameter values by repeat key. 3. Additionally master-/slave-function at remote system "CTRL+". |